



קוטר ציר [מ"מ]	קוטר מיסב מתאים	מק"ט	מידות [מ"מ]			משקל [ק"ג]
			B1	d2	B2	
17	20	H204	24	32	7	0.045
	20	H304	28	32	7	0.045
	20	H2304	31	32	7	0.05
20	25	H205	26	38	8	0.065
	25	H305	29	38	8	0.075
	25	H2305	35	38	8	0.09
25	30	H206	27	45	8	0.1
	30	H306	31	45	8	0.11
	30	H2306	38	45	8	0.125
30	35	H207	29	52	9	0.125
	35	H307	35	52	9	0.145
	35	H2307	43	52	9	0.16
35	40	H208	31	58	10	0.175
	40	H308	36	58	10	0.19
	40	H2308	46	58	10	0.225
40	45	H209	33	65	11	0.225
	45	H309	39	65	11	0.26
	45	H2309	50	65	11	0.3
45	50	H210	35	70	12	0.275
	50	H310	42	70	12	0.3
	50	H2310	55	70	12	0.35
50	55	H211	37	75	12	0.305
	55	H311	45	75	12	0.35
	55	H2311	59	75	12	0.4
55	60	H212	38	80	13	0.365
	60	H312	47	80	13	0.4
	60	H2312	62	80	13	0.45
60	65	H213	40	85	14	0.4
	65	H313	50	85	14	0.45
	65	H2313	65	85	14	0.55
65	75	H215	43	98	15	0.7
	75	H315	55	98	15	0.85
	75	H2315	73	98	15	1.05

קוטר ציר [מ"מ]	קוטר מיסב מתאים	מק"ט	מידות [מ"מ]			משקל [ק"ג]
			B1	d2	B2	
70	80	H216	46	105	17	0.85
	80	H316	59	105	17	1.05
	80	H2316	78	105	17	1.3
75	85	H217	50	110	18	1
	85	H317	63	110	18	1.2
	85	H2317	82	110	18	1.45
80	90	H218	52	120	18	1.15
	90	H318	65	120	18	1.4
	90	H2318	86	120	18	1.7
85	95	H219	55	125	19	1.35
	95	H319	68	125	19	1.55
	95	H2319	90	125	19	1.9
90	100	H220	58	130	20	1.45
	100	H320	71	130	20	1.7
	100	H2320	97	130	20	2.15
100	110	H222	81	145	21	2.25
	110	H322	63	145	21	1.95
	110	H2322	105	145	21	2.75
110	120	H3024	72	145	22	1.95
	120	H3124	88	155	22	2.65
	120	H2324	112	155	22	3.2
115	130	H3026	80	155	23	2.85
	130	H3126	92	165	23	3.65
	130	H2326	121	165	23	4.6
125	140	H3028	82	165	24	3.15
	140	H3128	97	180	24	4.35
	140	H2328	131	180	24	5.55
135	150	H3030	87	180	26	3.9
	150	H3130	111	195	26	5.5
	150	H2330	139	195	26	6.6
140	160	H3032	78	190	28	4.64
	160	H3132	93	190	28	5.2
	160	H2332	147	210	28	9.15

Bearings Tables; sponsored by NSK Ltd.

אומי נעילה AN וטבעות אבטחה AW, ראה עמ' 7-12