



UCF



UCF  
נעילת ברגים



EWF / UELF  
נעילה אקצנטרית

קוטר ציר [מ"מ]	*מק"ט	מידות [מ"מ]													בורג נעילה	עומסים [ניוטון]		[ק"ג כח]		משקל [ק"ג]
		L	J	A	A1	A2	N	B	B1	S	A0	Ha	A4	Cr		Cor	Cr	Cor		
12	UCF201	86	64	25.5	11	15	12	31	-	12.7	33.3	-	37.5	M 10	12800	6650	1300	675	0.7	
15	UCF202	86	64	25.5	11	15	12	31	-	12.7	33.3	-	37.5	M 10	12800	6650	1300	675	0.7	
17	UCF203	86	64	25.5	11	15	12	31	-	12.7	33.3	-	37.5	M 10	12800	6650	1300	675	0.6	
20	UCF204	86	64	25.5	11	15	12	31	43.7	12.7	33.3	34	41.6	M 10	12800	6650	1300	675	0.6	
25	UCF205	95	70	27	13	16	12	34.1	44.4	14.3	35.8	38	42.9	M 10	14000	7850	1430	800	0.8	
	UCF305	110	80	29	13	16	16	38	46.8	15	39	41	46.1	M 14	21200	10900	2160	1110	1.1	
30	UCF206	108	83	31	13	18	12	38.1	48.4	15.9	40.2	45	48.1	M 10	19500	11300	1980	1150	1	
	UCF306	125	95	32	15	18	16	43	50	17	44	49	50.5	M 14	26700	15000	2720	1530	1.6	
35	UCF207	117	92	34	15	19	14	42.9	51.1	17.5	44.4	51	51.3	M 12	25700	15300	2620	1560	1.4	
	UCF307	135	100	36	16	20	19	48	51.6	19	49	-	53.3	M 16	33500	19100	3400	1950	2	
40	UCF208	130	102	36	15	21	16	49.2	56.3	19	51.2	57	55.9	M 14	29100	17800	2970	1820	1.8	
	UCF308	150	112	40	17	23	19	52	57.1	19	56	-	60.3	M 16	40500	24000	4150	2450	2.7	
45	UCF209	137	105	38	16	22	16	49.2	56.3	19	52.2	62	56.9	M 14	32500	20400	3300	2080	2.2	
	UCF309	160	125	44	18	25	19	57	58.7	22	60	-	63.9	M 16	53000	32000	5400	3250	3.4	
50	UCF210	143	111	40	16	22	16	51.6	62.7	19	54.6	67	60.1	M 14	35000	23200	3600	2370	2.4	
	UCF310	175	132	48	19	28	23	61	66.6	22	67	-	70	M 20	62000	38500	6300	3900	4.5	
55	UCF211	162	130	43	18	25	19	55.6	71.4	22.2	58.4	73	68.6	M 16	43500	29200	4450	2970	3.6	
	UCF311	185	140	52	20	30	23	66	73	25	71	-	75.2	M 20	71500	45000	7300	4550	5.5	
60	UCF212	175	143	48	18	29	19	65.1	77.8	25.4	68.7	81	75.8	M 16	52500	36000	5350	3700	4.4	
	UCF312	195	150	56	22	33	23	71	79.4	26	78	-	81.45	M 20	82000	52000	8350	5300	6.5	
65	UCF213	187	149	50	22	30	19	65.1	85.7	25.4	69.7	87	81.55	M 16	57500	40000	5850	4100	5.5	
	UCF313	208	166	58	22	33	23	75	85.7	30	78	93	86.15	M 20	92500	60000	9450	6100	7.9	
70	UCF214	193	152	54	22	31	19	74.6	85.7	30.2	75.4	91	82.55	M 16	62000	44000	6350	4500	6.1	
	UCF314	226	178	61	25	36	25	78	92.1	33	81	-	93.95	M 22	104000	68000	10600	6950	9.5	
75	UCF215	200	159	56	22	34	19	77.8	92	33.3	78.5	97	88.7	M 16	66000	49500	6750	5050	6.9	
	UCF315	236	184	66	25	39	25	82	100	32	89	106	101.7	M22	113000	77000	11600	7850	12	
80	UCF216	208	165	58	22	34	23	82.6	-	33.3	83.3	-	-	M 20	72500	53000	7400	5400	8.1	
	UCF316	250	196	68	27	38	31	86	106.4	34	90	112	-	M 27	123000	86500	12500	8850	14	
85	UCF217	220	175	63	24	36	23	85.7	-	34.1	87.6	-	-	M 20	83500	64000	8500	6500	9.3	
	UCF317	260	204	74	27	44	31	96	109.5	40	100	119	-	M 27	133000	97000	13500	9850	16	
90	UCF218	235	187	68	24	40	23	96	-	39.7	96.3	-	-	M 20	96000	71500	9800	7300	11	
	UCF318	280	216	76	30	44	35	96	115.9	40	100	125	-	M 30	143000	107000	14500	11000	19	
95	UCF319	290	228	94	30	59	35	103	-	41	121	-	-	M 30	153000	119000	15600	12100	22	
100	UCF320	310	242	94	32	59	38	108	-	42	125	-	-	M 33	173000	141000	17700	14400	26	

Bearings Tables; sponsored by NSK Ltd.

\*מק"ט EWF הוחלף ל- UELF

המידה B1 מתייחסת לבתי מיסב מסדרת EWF/UELF

ניתן לקבל עם מיסב פנימי במידות אינצ'יות

ניתן לקבל עם מיסב פנימי קוד קוני ומתאם H23x+UKF..