



UCFL



UCFL
נעילת כרגים



EWFL / UELFL
נעילה אקצנטרית

קוטר ציר [מ"מ]	*מק"ט	מידות [מ"מ]												בורג נעילה	עומסים [ק"ג כח] [kgf]				משקל [ק"ג]	
		H	J	L	Ha	A	A1	A2	N	B	B1	S	Ao		A4	Cr	Cor	Cr		Cor
12	UCFL201	113	90	60	-	25.5	11	15	12	31	-	12.7	33.3	37.5	M 10	12800	6650	1300	675	0.6
15	UCFL202	113	90	60	-	25.5	11	15	12	31	-	12.7	33.3	37.5	M 10	12800	6650	1300	675	0.6
17	UCFL203	113	90	60	-	25.5	11	15	12	31	-	12.7	33.3	37.5	M 10	12800	6650	1300	675	0.5
20	UCFL204	113	90	60	-	25.5	11	15	12	31	43.7	12.7	33.3	41.6	M 10	12800	6650	1300	675	0.5
25	UCFL205	130	99	68	-	27	13	16	16	34.1	44.4	14.3	35.8	42.9	M 14	14000	7850	1430	800	0.6
	UCFL305	150	113	80	-	29	13	16	19	38	46.8	15	39	46.1	M 16	21200	10900	2160	1110	1.1
30	UCFL206	148	117	80	49	31	13	18	16	38.1	48.4	15.9	40.2	48.1	M 14	19500	11300	1980	1150	0.9
	UCFL306	180	134	90	-	32	15	18	23	43	50	17	44	50.5	M 20	26700	15000	2720	1530	1.5
35	UCFL 207	161	130	90	51	34	15	19	16	42.9	51.1	17.5	44.4	51.3	M 14	25700	15300	2620	1560	1.2
	UCFL307	185	141	100	-	36	16	20	23	48	51.6	19	49	53.3	M 20	33500	19100	3400	1950	1.9
40	UCFL 208	175	144	100	-	36	15	21	16	49.2	56.3	19	51.2	55.9	M 14	29100	17800	2970	1820	1.6
	UCFL308	200	158	112	-	40	17	23	23	52	57.1	19	56	60.3	M 20	40500	24000	4150	2450	2.5
45	UCFL 209	188	148	108	62	38	16	22	19	49.2	56.3	19	52.2	56.9	M 16	32500	20400	3300	2080	1.9
	UCFL309	230	177	125	-	44	18	25	25	57	58.7	22	60	63.9	M 22	53000	32000	5400	3250	3.4
50	UCFL 210	197	157	115	-	40	16	22	19	51.6	62.7	19	54.6	60.1	M 16	35000	23200	3600	2370	2.2
	UCFL310	240	187	140	-	48	19	28	25	61	66.6	22	67	70	M 22	62000	38500	6300	3900	4.4
55	UCFL 211	224	184	130	73	43	18	25	19	55.6	71.4	22.2	58.4	68.6	M 16	43500	29200	4450	2970	3.1
	UCFL311	250	198	150	-	52	20	30	25	66	73	25	71	75.2	M 22	71500	45000	7300	4550	5.1
60	UCFL 212	250	202	140	-	48	18	29	23	65.1	77.8	25.4	68.7	75.8	M 20	52500	36000	5350	3700	4
	UCFL312	270	212	160	-	56	22	33	31	71	79.4	26	78	81.45	M 27	82000	52000	8350	5300	6.1
65	UCFL 213	258	210	155	-	50	22	30	23	65.1	85.7	25.4	69.7	81.55	M 20	57500	40000	5850	4100	5
	UCFL313	295	240	175	-	58	25	33	31	75	85.7	30	78	86.15	M 27	92500	60000	9450	6100	7.8
70	UCFL 214	265	216	160	-	54	22	31	23	74.6	85.7	30.2	75.4	-	M 20	62000	44000	6350	4500	5.6
	UCLF 314	315	250	185	-	61	28	36	35	78	92.1	33	81	-	M 30	104000	68000	10600	6950	9
75	UCFL 215	275	225	165	-	56	22	34	23	77.8	92	33.3	78.5	-	M 20	66000	49500	6750	5050	6.2
	UCFL315	320	260	195	-	66	30	39	35	82	100	32	89	-	M 30	113000	77000	11600	7850	10
80	UCFL 216	290	233	180	-	58	22	34	25	82.6	-	33.3	83.3	-	M 22	72500	53000	7400	5400	8.2
	UCFL316	355	285	210	-	68	32	38	38	86	106.4	34	90	-	M 33	123000	86500	12500	8850	13
85	UCFL 217	305	248	190	-	63	24	36	25	85.7	-	34.1	87.6	-	M 22	83500	64000	8500	6500	9.3
	UCFL317	370	300	220	-	74	32	44	38	96	109.5	40	100	-	M 33	133000	97000	13500	9850	15
90	UCFL 218	320	265	205	-	68	24	40	25	96	-	39.7	96.3	-	M 22	96000	71500	9800	7300	11
	UCFL318	385	315	235	-	76	36	44	38	96	115.9	40	100	-	M 33	143000	107000	14500	11000	18
95	UCFL319	405	330	250	-	94	40	59	41	103	-	41	121	-	M 36	153000	119000	15600	12100	22
100	UCFL320	440	360	270	-	94	40	59	44	108	-	42	125	-	M 39	173000	141000	17700	14400	27

Bearings Tables; sponsored by NSK Ltd.

*מק"ט EWFL הוחלף ל- UELFL

המידה B1 מתייחסת לבתי מיסב מסדרת EWFL/UELFL

ניתן לקבל עם מיסב פנימי במידות אינצ'יות

ניתן לקבל עם מיסב פנימי קוד קוני ומתאם H23x...+UKFL