



UCT



UCT  
נעילת ברגים



EWT/UEL  
נעילה אקצנטרית

קוטר ציר [מ"מ]	מק"ט	מידות [מ"מ]															עומסים				משקל [ק"ג]	
		N1	L2	H2	N2	N	L3	A1	H1	H	L	A	A2	L1	B	B1	S	Cr [N]	Cor [N]	Cr [kgf]		Cor [kgf]
12	UCT201	16	12	51	32	19	51	12	76	89	94	32	21	61	31	-	12.7	12800	6650	1300	675	0.8
15	UCT202	16	12	51	32	19	51	12	76	89	94	32	21	61	31	-	12.7	12800	6650	1300	675	0.8
17	UCT203	16	12	51	32	19	51	12	76	89	94	32	21	61	31	-	12.7	12800	6650	1300	675	0.8
20	UCT204	16	12	51	32	19	51	12	76	89	94	32	21	61	31	-	12.7	12800	6650	1300	675	0.8
25	UCT205	16	12	51	32	19	51	12	76	89	97	32	24	62	34.1	44.4	14.3	14000	7850	1430	800	0.9
	UCT305	16	14	62	36	26	65	12	80	89	122	36	26	76	38	46.8	15	21200	10900	2160	1110	1.4
30	UCT206	16	12	56	37	22	57	12	89	102	113	37	28	70	38.1	48.4	15.9	19500	11300	1980	1150	1.3
	UCT306	18	16	70	41	28	74	16	90	100	137	41	28	85	43	50	17	26700	15000	2720	1530	1.8
35	UCT207	16	15	64	37	22	64	12	89	102	129	37	30	78	42.9	51.1	17.5	25700	15300	2620	1560	1.7
	UCT307	20	17	75	45	30	80	16	100	111	150	45	32	94	48	51.6	19	33500	19100	3400	1950	2.4
40	UCT208	19	18	83	49	29	83	16	102	114	144	49	33	88	49.2	56.3	19	29100	17800	2970	1820	2.3
	UCT308	22	19	83	50	32	89	18	112	124	162	50	34	100	52	57.1	19	40500	24000	4150	2450	3
45	UCT209	19	18	83	49	29	83	16	102	117	145	49	35	88	49.2	56.3	19	32500	20400	3300	2080	2.4
	UCT309	24	20	90	55	34	97	18	125	138	178	55	38	110	57	58.7	22	53000	32000	5400	3250	4
50	UCT210	19	18	83	49	29	86	16	102	117	151	49	37	92	51.6	62.7	19	35000	23200	3600	2370	2.6
	UCT310	27	22	98	61	37	106	20	140	151	192	61	40	118	61	66.6	22	62000	38500	6300	3900	5
55	UCT211	25	21	102	64	35	95	22	130	146	171	64	38	106	55.6	71.4	22.2	43500	29200	4450	2970	3.8
	UCT311	29	23	105	66	39	115	22	150	163	207	66	44	127	66	73	25	71500	45000	7300	4550	6.4
60	UCT212	32	21	102	64	35	102	22	130	146	194	64	42	119	65.1	77.8	25.4	52500	36000	5350	3700	4.7
	UCT312	31	25	113	71	41	123	22	160	178	220	71	46	135	71	79.4	26	82000	52000	8350	5300	7.6
65	UCT213	32	23	111	70	41	121	26	151	167	224	70	44	137	65.1	85.7	25.4	57500	40000	5850	4100	7
	UCT313	32	27	116	70	43	134	26	170	190	238	80	50	146	75	85.7	30	92500	60000	9450	6100	9.7
70	UCT214	32	23	111	70	41	121	26	151	167	224	70	46	137	74.6	85.7	30.2	62000	44000	6350	4500	7.3
	UCT314	36	27	130	85	46	140	26	180	202	252	90	52	155	78	92.1	33	104000	68000	10600	6950	11
75	UCT215	32	23	111	70	41	121	26	151	167	232	70	48	140	77.8	92.1	33.3	66000	49500	6750	5050	7.7
	UCT315	36	27	132	85	46	150	26	192	216	262	90	55	160	82	100	32	113000	77000	11600	7850	14
80	UCT216	32	23	111	70	41	121	26	165	184	235	70	51	140	82.6	-	33.3	72500	53000	7400	5400	8.4
	UCT316	42	30	150	98	53	160	30	204	230	282	102	60	174	86	106.4	34	123000	86500	12500	8850	16
85	UCT217	38	31	124	73	48	157	30	173	198	260	73	54	162	85.7	-	34.1	83500	64000	8500	6500	11
	UCT317	42	32	152	98	53	170	32	214	240	298	102	64	183	96	109.5	40	133000	97000	13500	9850	20
90	UCT318	46	32	160	106	57	175	32	228	255	312	110	66	192	96	115.9	40	143000	107000	14500	11000	22
95	UCT319	46	33	165	106	57	180	35	240	270	322	110	72	197	103	122.3	41	153000	119000	15600	12100	25
100	UCT320	48	34	175	115	59	200	35	260	290	345	120	75	210	108	128.6	42	173000	141000	17700	14400	32

Bearings Tables; sponsored by NSK Ltd.

המידה B1 מתייחסת לבתי מיסב מסדרת EWT/UEL  
ניתן לקבל עם מיסב פנימי במידות אינצ'יות  
ניתן לקבל עם מיסב פנימי קדח קוני ומתאם UKT...+H23xx