


SN

קוטר ציר d1 [מ"מ]	מק"ט	מידות [מ"מ]										הברגה		משקל [ק"ג]
		H	H1	l	a	b	c	M	u	v	t nominal	S מ"מ	אינץ'	
20	SN505	40	75	67	165	46	22	130	15	20	M8	M12	1/2	1.1
25	SN506	50	90	77	185	52	22	150	15	20	M8	M12	1/2	1.7
30	SN507	50	95	82	185	52	22	150	15	20	M10	M12	1/2	1.9
35	SN508	60	110	85	205	60	25	170	15	20	M10	M12	1/2	2.6
40	SN509	60	112	85	205	60	25	170	15	20	M10	M12	1/2	2.8
45	SN510	60	115	90	205	60	25	170	15	20	M10	M12	1/2	3.0
50	SN511	70	130	95	255	70	28	210	18	23	M12	M16	5/8	4.5
55	SN512	70	135	105	255	70	30	210	18	23	M12	M16	5/8	5
60	SN513	80	150	110	275	80	30	230	18	23	M12	M16	5/8	5.6
65	SN515	80	155	115	280	80	30	230	18	23	M12	M16	5/8	7
70	SN516	95	175	120	315	90	32	260	22	27	M16	M20	3/4	9
75	SN517	95	185	125	320	90	32	260	22	27	M16	M20	3/4	10
80	SN518	100	195	145	345	100	35	290	22	27	M16	M20	3/4	13
85	SN519	112	210	140	345	100	35	290	22	27	M16	M20	3/4	15
90	SN520	112	218	160	380	110	40	320	26	32	M20	M24	7/8	18.5
100	SN522	125	240	175	410	120	45	350	26	32	M20	M24	7/8	20
110	SN524	140	270	185	410	120	45	350	26	32	M20	M24	7/8	24.5
115	SN526	150	290	190	445	130	50	380	28	36	M24	M24	1	30
125	SN528	150	305	205	500	150	50	420	33	42	M24	M30	1 1/4	38
135	SN530	160	325	220	530	160	60	450	33	42	M24	M30	1 1/4	46
140	SN532	170	345	235	550	160	60	470	33	42	M24	M30	1 1/4	50



ZF  
אטם קפיצי

בית מיסב חצוי	מיסבים	מתאמים קוניים	טבעות מרווח		אטם	כמות
			טבעת	כמות לטס		
SN505	1205K	H205	2	FR5/52	ZF05	2
	2205K	H305	1	FR7/52	ZF05	2
SN506	1206K	H206	2	FR7/62	ZF06	2
	2206K	H306	1	FR10/62	ZF06	2
SN507	1207K	H207	2	FR8/72	ZF07	2
	2207K	H307	1	FR10/72	ZF07	2
SN508	1208K	H208	2	FR7.5/80	ZF08	2
	22208CK	H308	1	FR10/80	ZF08	2
SN509	1209K	H209	2	FR6/85	ZF09	2
	2209K	H309	1	FR8/85	ZF09	2
	22209CK	H309	1	FR8/85	ZF09	2
SN510	1210K	H210	2	FR6.5/90	ZF10	2
	2210K	H310	1	FR10/90	ZF10	2
	22210CK	H310	1	FR10/90	ZF10	2
SN511	1211K	H211	2	FR6/100	ZF11	2
	2211K	H311	1	FR8/100	ZF11	2
	22211CK	H311	1	FR8/100	ZF11	2
SN512	1212K	H212	2	FR8/110	ZF12	2
	2212K	H312	1	FR10/110	ZF12	2
	22212CK	H312	1	FR10/110	ZF12	2
SN513	1213K	H213	2	FR10/120	ZF13	2
	2213K	H313	1	FR12/120	ZF13	2
	22213CK	H313	1	FR12/120	ZF13	2
SN515	1215K	H215	2	FR8/130	ZF15	2
	2215K	H315	1	FR10/130	ZF15	2
	22215CK	H315	1	FR10/130	ZF15	2
SN516	1216K	H216	2	FR8.5/140	ZF16	2
	2216K	H316	1	FR10/140	ZF16	2
	22216CK	H316	1	FR10/140	ZF16	2

בית מיסב חצוי	מיסבים	מתאמים קוניים	טבעות מרווח		אטם	כמות
			טבעת	כמות לטס		
SN517	1217K	H217	2	FR9/150	ZF17	2
	2217K	H317	1	FR10/150	ZF17	2
	22217CK	H317	1	FR10/150	ZF17	2
SN518	1218K	H218	2	FR16.2/160	ZF18	2
	2218K	H318	2	FR11.2/160	ZF18	2
	22218CK	H318	2	FR11.2/160	ZF18	2
	23218CK	H2318	1	FR10/160	ZF18	2
SN519	1219K	H219	2	FR10.5/170	ZF19	2
	2219K	H319	1	FR10/170	ZF19	2
	22219K	H319	1	FR10/170	ZF19	2
	23219K	H2319	2	FR10.5/170	ZF19	2
SN520	1220K	H220	2	FR18.1/180	ZF20	2
	2220K	H320	2	FR12.1/180	ZF20	2
	22220CK	H320	2	FR12.1/180	ZF20	2
	23220CK	H2320	1	FR10/180	ZF20	2
SN522	1222K	H222	2	FR21/200	ZF22	2
	2222CK	H322	2	FR13.5/200	ZF22	2
	22222CK	H322	2	FR13.5/200	ZF22	2
	23222CK	H2322	1	FR10/200	ZF22	2
SN524	22224CK	H3124	2	FR14/215	ZF24	2
	23224CK	H2324	1	FR10/215	ZF24	2
SN526	22226CK	H3126	2	FR13/230	ZF26	2
	23226CK	H2326	1	FR10/230	ZF26	2
SN528	22228CK	H3128	2	FR15/250	ZF28	2
	23228CK	H2328	1	FR10/250	ZF28	2
SN530	22230CK	H3130	2	FR16.5/270	ZF30	2
	23230CK	H2330	1	FR10/270	ZF30	2
SN532	22232CK	H3132	2	FR17/290	ZF32	2
	23232CK	H2332	1	FR10/290	ZF32	2

למניעת גירוז יתר מומלץ להשתמש ביחידות גירוז אוטומטיות, המספקות גריז בכמות דרושה ובקצב אחיד.

לקבלת נתונים על יחידת הגירוז ראה עמ' 9-12.

נתוני מיסבים: בפרק 1 עמ' 25, 24, 23, 22, 7, 6.  
נתוני מתאמים קוניים, ראה עמ' 5-2.

המלצות אחזקה והתקנה ראה עמ' 2-2.

