



B22400HL

קוטר ציר [מ"מ]	מק"ט	מידות [מ"מ]									עומסים [N]		מהירות מירבית [סל"ד]
		B	C	E	H	M	N	R	T	Y	סטטי Co	דינמי C	
1	B22416HL	60.325	30.18	50.8	65.09	50.8	33.20	1.17	12.7	25.40	66100	51200	3500
25	B224M25HL	60.325	30.18	50.8	65.09	50.8	33.20	1.17	12.7	25.40	66100	51200	3500
1-3/16	B22419HL	66.675	33.32	58.7	68.26	55.6	38.91	1.57	12.7	26.99	80500	60900	3000
1-1/4	B22420HL	66.675	33.32	58.7	68.26	55.6	38.91	1.57	12.7	26.99	80500	60900	3000
30	B224M30HL	66.675	33.32	58.7	68.26	55.6	38.91	1.57	12.7	26.99	80500	60900	3000
1-7/16	B22423HL	71.996	33.27	63.5	73.02	63.5	44.32	1.57	15.9	27.78	93200	64900	2750
1-1/2	B22424HL	71.996	33.27	63.5	73.02	63.5	44.32	1.57	15.9	27.78	93200	64900	2750
35	B224M35HL	71.996	33.27	63.5	73.02	63.5	44.32	1.57	15.9	27.78	93200	64900	2750
1-5/8	B22426HL	84.998	40.08	73.0	79.38	69.8	51.48	1.57	15.9	30.96	127700	89800	2350
1-11/16	B22427HL	84.998	40.08	73.0	79.38	69.8	51.48	1.57	15.9	30.96	127700	89800	2350
1-3/4	B22428HL	84.998	40.08	73.0	79.38	69.8	51.48	1.57	15.9	30.96	127700	89800	2350
40	B224M40HL	84.998	40.08	73.0	79.38	69.8	51.48	1.57	15.9	30.96	127700	89800	2350
1-15/16	B22431HL	90.000	38.76	81.0	79.38	74.6	58.59	1.98	15.9	30.96	147700	94300	2150
2	B22432HL	90.000	38.76	81.0	79.38	74.6	58.59	1.98	15.9	30.96	147700	94300	2150
45	B224M45HL	90.000	38.76	81.0	79.38	74.6	58.59	1.98	15.9	30.96	147700	94300	2150
50	B224M50HL	90.000	38.76	81.0	79.38	74.6	58.59	1.98	15.9	30.96	147700	94300	2150
2-3/16	B22435HL	100.000	42.06	88.9	84.14	85.7	66.55	1.57	19.0	31.75	197500	117400	1950
2-1/4	B22436HL	100.000	42.06	88.9	84.14	85.7	66.55	1.57	19.0	31.75	197500	117400	1950
55	B224M55HL	100.000	42.06	88.9	84.14	85.7	66.55	1.57	19.0	31.75	197500	117400	1950
2-7/16	B22439HL	110.000	44.45	98.4	88.90	92.1	73.69	1.98	20.6	33.34	238000	139700	1750
2-1/2	B22440HL	110.000	44.45	98.4	88.90	92.1	73.69	1.98	20.6	33.34	238000	139700	1750
60	B224M60HL	110.000	44.45	98.4	88.90	92.1	73.69	1.98	20.6	33.34	238000	139700	1750
2-11/16	B22443HL	129.977	53.98	115.1	101.60	106.4	85.60	1.98	20.6	39.69	318000	185900	1500
2-3/4	B22444HL	129.977	53.98	115.1	101.60	106.4	85.60	1.98	20.6	39.69	318000	185900	1500
2-15/16	B22447HL	129.977	53.98	115.1	101.60	106.4	85.60	1.98	20.6	39.69	318000	185900	1500
3	B22448HL	129.977	53.98	115.1	101.60	106.4	85.60	1.98	20.6	39.69	318000	185900	1500
65	B224M65HL	129.977	53.98	115.1	101.60	106.4	85.60	1.98	20.6	39.69	318000	185900	1500
70	B224M70HL	129.977	53.98	115.1	101.60	106.4	85.60	1.98	20.6	39.69	318000	185900	1500
75	B224M75HL	129.977	53.98	115.1	101.60	106.4	85.60	1.98	20.6	39.69	318000	185900	1500
3-3/16	B22451HL	149.974	58.75	135.7	111.12	127.0	100.97	3.18	21.4	43.66	403400	226800	1250
3-7/16	B22455HL	149.974	58.75	135.7	111.12	127.0	100.97	3.18	21.4	43.66	403400	226800	1250
3-1/2	B22456HL	149.974	58.75	135.7	111.12	127.0	100.97	3.18	21.4	43.66	403400	226800	1250
80	B224M80HL	149.974	58.75	135.7	111.12	127.0	100.97	3.18	21.4	43.66	403400	226800	1250
85	B224M85HL	149.974	58.75	135.7	111.12	127.0	100.97	3.18	21.4	43.66	403400	226800	1250
3-11/16	B22459HL	179.974	69.85	161.9	128.59	150.0	115.85	3.18	24.6	50.80	609400	351800	1100
3-15/16	B22463HL	179.974	69.85	161.9	128.59	150.0	115.85	3.18	24.6	50.80	609400	351800	1100
4	B22464HL	179.974	69.85	161.9	128.59	150.0	115.85	3.18	24.6	50.80	609400	351800	1100
90	B224M90HL	179.974	69.85	161.9	128.59	150.0	115.85	3.18	24.6	50.80	609400	351800	1100
100	B224M100HL	179.974	69.85	161.9	128.59	150.0	115.85	3.18	24.6	50.80	609400	351800	1100